



2011 RAM MAX GROSS COMBINED WEIGHT RATING (GCWR) (LB)



Engine	Trans.	Axle Ratio	3,000	6,000	9,000	12,000	15,000	18,000	21,000	24,000	27,000	30,000
RAM 2500	5.7L V8	A5	3.73	15,000								
		A5	4.10	18,000								
	6.7L Diesel	M6	3.42	19,000								
		M6	3.73	20,000								
		A5	3.42	17,000								
		A5	3.73	19,000								
		A5	4.10	22,000								
		A5	4.56	17,000								
RAM 3500	6.7L Diesel	M6	3.42	19,000								
		M6	3.73	21,000								
	6.7L Diesel	A5	3.42	17,000								
		A5	3.73	21,000								
		A5	4.10	Short Box / SRW 24,000								
		A5	4.10	Short Box / DRW / Max Tow 26,000								
		A5	4.10	Long Box / DRW / Max Tow 30,000								

NOTE: All figures shown in pounds. To convert to kilograms multiply number by 0.4536.



2011 RAM 2500 MAXIMUM TRAILER WEIGHT CAPABILITY *



Drive	Box	Cab	Axle Ratio	2,500	5,000	7,500	10,000	12,500	15,000	17,500	20,000	22,500	22,750
4X2	Long	Regular	4.10	15,500									
		Crew	4.10	15,050									
	Short	Crew	4.10	15,200									
		Mega	4.10	14,800									
4X4	Long	Regular	4.10	15,050									
		Crew	4.10	14,650									
	Short	Crew	4.10	14,700									
		Mega	4.10	14,300									

CUMMINS
TURBO
DIESEL

2011 RAM 3500 MAXIMUM TRAILER WEIGHT CAPABILITY *



4X2	Long	Regular	4.10	BEST-IN-CLASS † 22,750									
		Crew	4.10	19,200									
	Short	Crew	4.10	17,150									
		Mega	4.10	18,450									
4X4	Long	Regular	4.10	22,300									
		Crew	4.10	20,100									
	Short	Crew	4.10	16,750									
		Mega	4.10	18,050									

NOTE: All figures shown in pounds. To convert to kilograms multiply number by 0.4536. *Maximum capability ratings shown, based on properly equipped trucks, optional equipment maybe necessary. Weight of additional options, equipment, passengers and cargo must be deducted from these weights. See your Ram retailer for details. † 2012MY rating. Based on 350/3500 pickups when properly equipped. Available for order.