

All-New 2019 Ram 1500

TOWING* (Conventional ball & hitch) (SAE J2807 Compliant) kg (lb) - Maximum ratings when properly equipped.				Quad Cab®		Crew Cab			
				1.9m (6'4") Box		1.7m (5'7") Box		1.9m (6'4") Box	
Engine	Auto Trans	Axle Ratio	GCWR	4x2	4x4	4x2	4x4	4x2	4x4
3.6L Pentastar® VVT V6 with eTorque	8-speed	3.21	5398 (11900)	3053 (6730)	2908 (6410)	2957 (6520)	2889 (6370)	2948 (6500)	2835 (6250)
		3.55	5851 (12900)	3506 (7730)	3361 (7410)	3411 (7520)	3342 (7370)	3402 (7500)	3289 (7250)
		3.92	5851 (12900)	3506 (7730)	3361 (7410)	3411 (7520)	3343 (7370)	3402 (7500)	3289 (7250)
5.7L HEMI® V8	8-speed	3.21	6305 (13900)	3860 (8510)	3797 (8370)	3828 (8440)	3738 (8240)	3824 (8430)	3692 (8140)
		3.92	7711 (17000)	5266 (11610)	5203 (11470)	5234 (11540)	5144 (11340)	5230 (11530)	5098 (11240)
5.7L HEMI® V8 with eTorque	8-speed	3.21	6305 (13900)	3837 (8460)	3733 (8230)	3778 (8330)	3697 (8150)	3760 (8290)	3638 (8020)
		3.92	7711 (17000)	5244 (11560)	5139 (11330)	5185 (11430)	5103 (11250)	5166 (11390)	5044 (11120)
		3.92	8255 (18200)	5783 (12750)					
PAYLOAD* (SAE J20807 Compliant) kg (lb) - Maximum ratings when properly equipped				Quad Cab		Crew Cab			
				1.9m (6'4") Box		1.7m (5'7") Box		1.9m (6'4") Box	
Engine	Auto Trans	Axle Ratio	GVWR	4x2	4x4	4x2	4x4	4x2	4x4
3.6L Pentastar® VVT V6 with eTorque	8-speed	3.21 or 3.55 or 3.92	3084 (6800)		776 (1710)				
		3.21 or 3.55 or 3.92	3130 (6900)	953 (2100)		875 (1930)	803 (1770)	853 (1880)	757 (1670)
		3.21 or 3.55	3221 (7100)	1043 (2300)					
5.7L HEMI® V8	8-speed	3.21 or 3.92	3130 (6900)	862 (1900)		839 (1850)		830 (1830)	
		3.21 or 3.92	3221 (7100)		894 (1970)		835 (1840)		807 (1780)
5.7L HEMI® V8 with eTorque	8-speed	3.21 or 3.92	3130 (6900)	830 (1830)		789 (1740)		767 (1690)	
		3.21 or 3.92	3221 (7100)		826 (1820)		807 (1780)		762 (1680)

* Information subject to change. All weights are in kilograms (pounds). Please visit www.rambodybuilder.com for full specifications

Payload and Max Trailer Weights are ESTIMATED values. All weights are shown in pounds unless otherwise stated. Payload and Max Trailer Weight values are rounded to the nearest 10 lb.

Payload = GVWR – Base Weight. Trailer Weight Rating and Tow Vehicle Trailering Weight are calculated as specified in SAE J2807. Passenger Weight = 300 lb. Options Weight is option content above 33 percent of sales volume.

Trailer equipment weight = Class IV receiver hitch is 11.1 lb (if not already included in options weight). Trailer Hitch is 10 lb if TWR is less or equal to 5,000 lb and 65 lb if TWR is greater than 5,000 lb.

Payload and Trailer Weight Rating are mutually exclusive. GAWRs, GVWRs and GCWRs should never be exceeded.

The recommended tongue weight for a conventional hitch is 10 percent of the gross trailer weight. The maximum tongue weight for Class IV receiver hitch is limited to 1,100lb.

Weight Distributing Hitch is recommended for trailers over 5,000 lb.

